



Typ	Rozmery /mm/						Utiahnutie spojky			Tlak na povrchy		
	d	D	D1	H	H1	H2	Mv	Nm	Skrutka	Nm	P hriadel' N/mm2	Fa kN
ZKPP-024	24	50	20	23	19,5	14	M5	4,9	6	170 210 250	286	15,0 18,5 21,0
			21							300		15,7
ZKPP-030	30	60	25	25	21,5	16	M5	4,9	7	340 380	233	23,7 26,7
			26							440		27,0
ZKPP-036	36	72	30	27,5	23,5	18	M6	11,8	5	570 630	307	38,0 43,0
			28							620		44,0
ZKPP-044	44	80	35	29,5	25,5	20	M6	11,8	7	780 860	317	49,0 54,0
			31							940		48,8
ZKPP-050	50	90	40	31,5	27,5	22	M6	11,8	8	1160 1380	289	58,8 69,0
			32							1160		48,0
ZKPP-055	55	100	45	34,5	30,5	23	M6	11,8	8	1520 1880	252	61,7 77,0
			38							1850		69,0
ZKPP-062	62	110	50	34,5	30,5	23	M6	11,8	10	2200 2400	279	80,9 90,0
			48							2000		71,2
ZKPP-068	68	115	55	34,5	30,5	23	M6	11,8	10	2500 3150	255	80,9 95,7
			50							2500		94,4
ZKPP-075	75	138	60	37,8	32,5	25	M8	29,4	7	3200 3950	273	111,0 126,0
			55							3200		99,3
ZKPP-080	80	145	65	37,8	32,5	25	M8	29,4	7	3900 4600	256	115,0 130,0
			60							4750		141,0
ZKPP-090	90	155	70	44,3	39	30	M8	29,4	10	6000 7250	271	60,0 178,0
			65							6900		163,0
ZKPP-100	100	170	75	49,3	44	34	M8	29,4	12	7500 9000	258	182,0 202,0
			70							7200		185,0
ZKPP-110	110	185	80	56,4	50	39	M10	57,8	9	9000 10800	244	207,0 221,0
			75							11000		240,0
ZKPP-125	125	215	90	60,4	54	42	M10	57,8	12	13000 15000	266	262,0 285,0
			85							15100		308,0
ZKPP-140	140	230	100	68	60,5	46	M12	98	10	17600 20100	264	331,0 357,0
			105							22000		366,0
ZKPP-155	155	263	110	72	64,5	50	M12	98	12	25000 28000	263	392,0 417,0
			115							31000		513,0
ZKPP-165	165	290	120	81	71	56	M16	245	8	25000 39000	277	544,0 564,0
			125									